


IGBT Module-Dual

150 A, 1200V


PDMB150B12C

PDMB150B12C2

□ 回路図 : CIRCUIT



□ 外形寸法図 : OUTLINE DRAWING



Dimension: [mm]

□ 最大定格 : MAXIMUM RATINGS (T<sub>c</sub>=25°C)

Item	Symbol	Rated Value	Unit
コレクタ・エミッタ間電圧 Collector-Emmitter Voltage	V <sub>CEs</sub>	1,200	V
ゲート・エミッタ間電圧 Gate-Emmitter Voltage	V <sub>GEs</sub>	±20	V
コレクタ電流 Collector Current	DC	I <sub>c</sub> 150	A
	1ms	I <sub>CP</sub> 300	
コレクタ損失 Collector Power Dissipation	P <sub>c</sub>	730	W
接合温度 Junction Temperature Range	T <sub>j</sub>	-40~+150	°C
保存温度 Storage Temperature Range	T <sub>stg</sub>	-40~+125	°C
絶縁耐圧(Terminal to Base AC, 1minute) Isolation Voltage	V <sub>iso</sub>	2,500	V <sub>(RMS)</sub>
締め付けトルク Mounting Torque	Module Base to Heatsink Busbar to Main Terminal	3 (30.6)	
		PDMB150B12C 3 (30.6)	PDMB150B12C2 2 (20.4)
			N·m (kgf·cm)

□ 電気的特性 : ELECTRICAL CHARACTERISTICS (T<sub>c</sub>=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
コレクタ遮断電流 Collector-Emmitter Cut-Off Current	I <sub>CEs</sub>	V <sub>CE</sub> =1200V, V <sub>GE</sub> =0V	-	-	3.0	mA
ゲート漏れ電流 Gate-Emmitter Leakage Current	I <sub>GES</sub>	V <sub>GE</sub> =±20V, V <sub>CE</sub> =0V	-	-	1.0	μA
コレクタ・エミッタ飽和電圧 Collector-Emmitter Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>c</sub> =150A, V <sub>GE</sub> =15V	-	1.9	2.4	V
ゲートしきい値電圧 Gate-Emmitter Threshold Voltage	V <sub>GE(th)</sub>	V <sub>CE</sub> =5V, I <sub>c</sub> =150mA	4.0	-	8.0	V
入力容量 Input Capacitance	C <sub>ies</sub>	V <sub>CE</sub> =10V, V <sub>GE</sub> =0V, f=1MHz	-	12,600	-	pF
スイッチング時間 Switching Time	上昇時間 Rise Time	V <sub>CC</sub> =600V R <sub>L</sub> =4Ω R <sub>f</sub> =3.6Ω V <sub>CE</sub> =±15V	-	0.25	0.45	μs
	ターンオン時間 Turn-on Time		-	0.40	0.70	
	下降時間 Fall Time		-	0.25	0.35	
	ターンオフ時間 Turn-off Time		-	0.80	1.10	

□ フリーホイールダイオードの特性 : FREE WHEELING DIODE RATINGS & CHARACTERISTICS (T<sub>c</sub>=25°C)







Item	Symbol	Rated Value	Unit			
順電流 Forward Current	DC	I <sub>F</sub> 150	A			
	1ms	I <sub>FM</sub> 300				
Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
順電圧 Peak Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =150A, V <sub>CE</sub> =0V	-	1.9	2.4	V
逆回復時間 Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> =150A, V <sub>CE</sub> =-10V di/dt=300A/μs	-	0.2	0.3	μs

□ 熱的特性 : THERMAL CHARACTERISTICS

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
熱抵抗 Thermal Impedance	IGBT	Rth(j-c) Junction to Case	-	-	0.16	°C/W
	Diode		-	-	0.32	

PDMB 150B12

PDMB 150B12C



PDMB150B12

PDMB150B12C

Fig.7- Series Gate Impedance vs. Switching Time (Typical)




Fig.8- Forward Characteristics of Free Wheeling Diode (Typical)




Fig.9- Reverse Recovery Characteristics (Typical)




Fig.10- Reverse Bias Safe Operating Area




Fig.11- Transient Thermal Impedance

