

Relay base - ECOR-2-BSC2-RT/2X21



2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

ECOR-2 relay base, for industrial relays with two changeover contacts, bolt connection, for mounting on NS 35/7,5



Relay base - ECOR-2-BSC2-RT/2X21



2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Commercial Data

Order Key	2908341
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	*****
Product Key	CK6313
GTIN	4055626293097
Weight per Piece (including packing)	43.98 g
Weight per Piece (excluding packing)	40.35 g
Customs tariff number	85366990
Country of origin	CN

Technical Data

Electrical properties

Nominal voltage U_N	250 V AC/DC
Nominal current I_N	12 A

Connection data

Input side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Output side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Dimensions

Width	25 mm
Height	68.5 mm
Depth	63 mm (ECOR-RHM-2)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Relay base - ECOR-2-BSC2-RT/2X21



2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Approvals

CSA 

cUL Recognized 

UL Recognized 

EAC 

cULus Recognized

Relay base - ECOR-2-BSC2-RT/2X21



2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Classifications

ECLASS

ECLASS-9.0	27371603
ECLASS-10.0.1	27371603
ECLASS-11.0	27371603

ETIM

ETIM 6.0	EC001456
----------	----------

UNSPSC

UNSPSC 19.0	39122335
UNSPSC 20.0	39122335
UNSPSC 21.0	39122335

Relay base - ECOR-2-BSC2-RT/2X21



2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Relay base - ECOR-2-BSC2-RT/2X21



2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Accessories

Wire bridge

Wire bridge - DB 50- 90 BU - 2821180

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: blue



Wire bridge

Wire bridge - DB 50- 90 BK - 2820916

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: black



Relay base - ECOR-2-BSC2-RT/2X21

2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Wire bridge

Wire bridge - DB 50- 90 GY - 2820929

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: gray



Single relay

Single relay - REL-IR-BL/L- 12DC/2X21 - 1109547



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 12 V DC

Relay base - ECOR-2-BSC2-RT/2X21

2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Single relay

Single relay - REL-IR-BL- 24DC/2X21 - 1032470



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test key, mechanical switch position indicator, polarity A1+, A2-, input voltage: 24 V DC

Single relay

Single relay - REL-IR-BL/L- 24DC/2X21 - 1032526



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V DC

Relay base - ECOR-2-BSC2-RT/2X21

2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Single relay

Single relay - REL-IR-BL/L- 48DC/2X21 - 1109548



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 48 V DC

Single relay

Single relay - REL-IR-BL/L-110DC/2X21 - 1109550



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 110 V DC

Relay base - ECOR-2-BSC2-RT/2X21

2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Single relay

Single relay - REL-IR-BL/L-125DC/2X21 - 1109553



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 125 V DC

Single relay

Single relay - REL-IR-BL/L-220DC/2X21 - 1109554



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 220 V DC

Relay base - ECOR-2-BSC2-RT/2X21

2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Single relay

Single relay - REL-IR-BL/L- 24AC/2X21 - 1109555



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V AC

Single relay

Single relay - REL-IR-BL/L-115AC/2X21 - 1109556



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 115 V AC

Relay base - ECOR-2-BSC2-RT/2X21

2908341

<https://www.phoenixcontact.com/sg/products/2908341>

Single relay

Single relay - REL-IR-BL-230AC/2X21 - 1032528



Plug-in industrial relay in basic design with power contacts, 2 changeover contacts, test key, mechanical switch position indicator, input voltage: 230 V AC

Single relay

Single relay - REL-IR-BL/L-230AC/2X21 - 1032530



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 230 V AC

Relay base - ECOR-2-BSC2-RT/2X21

2908341

<https://www.phoenixcontact.com/sg/products/2908341>



Relay retaining bracket

Relay retaining bracket - ECOR-RHM-2L - 1047026



Relay retaining bracket, wire model, suitable for ECOR-2... relay base when used with REL-IR-BL... relays

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.
105 Eunos Avenue 3, #04-00
Singapore 409836
+65 6228 4900
marketing@phoenixcontact.com.sg