

SKKT 330, SKKH 330



SEMIPACK® 3 1)

Thyristor / Diode Modules

SKKH 330

SKKT 330

Features

- Heat transfer through aluminium nitride ceramic isolated metal baseplate
- Precious metal pressure contacts for high reliability
- Thyristor with amplifying gate
- UL recognized, file no. E 63 532

Typical Applications

- DC motor control (e. g. for machine tools)
- Temperature control (e. g. for ovens, chemical processes)
- Professional light dimming (studios, theaters)

1) Discontinued version, redesigned version already available

2) See the assembly instruction

3) The screws must be lubricated

V_{RSM} V	V_{RRM}, V_{DRM} V	$I_{TRMS} = 510 \text{ A}$ (maximum value for continuous operation) $I_{TAV} = 330 \text{ A}$ (sin. 180; $T_c = 80 \text{ }^{\circ}\text{C}$)		
900	800	SKKT 330/08E	SKKH 330/08E	
1300	1200	SKKT 330/12E	SKKH 330/12E	
1500	1400	SKKT 330/14E	SKKH 330/14E	
1700	1600	SKKT 330/16E	SKKH 330/16E	
1900	1800	SKKT 330/18E	SKKH 330/18E	







Symbol	Conditions	Values	Units
I_{TAV}	sin. 180; $T_c = 85 \text{ (100) }^{\circ}\text{C}$	305 (225)	A
I_D	P16/200F; $T_a = 35 \text{ }^{\circ}\text{C}$; B2 / B6	520 / 650	A
I_{RMS}	P16/200F; $T_a = 35 \text{ }^{\circ}\text{C}$; W1 / W3	585 / 3 * 485	A
I_{TSM}	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; 10 ms	9500	A
	$T_{vj} = 130 \text{ }^{\circ}\text{C}$; 10 ms	8000	A
i^2t	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; 8,3 ... 10 ms	451000	A ² s
	$T_{vj} = 130 \text{ }^{\circ}\text{C}$; 8,3 ... 10 ms	320000	A ² s
V_T	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; $I_T = 750 \text{ A}$	max. 1,4	V
$V_{T(TO)}$	$T_{vj} = 130 \text{ }^{\circ}\text{C}$	max. 0,8	V
r_T	$T_{vj} = 130 \text{ }^{\circ}\text{C}$	max. 0,6	mΩ
I_{DD}, I_{RD}	$T_{vj} = 130 \text{ }^{\circ}\text{C}$; $V_{RD} = V_{RRM}$; $V_{DD} = V_{DRM}$	max. 50	mA
t_{gd}	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; $I_G = 1 \text{ A}$; $di_G/dt = 1 \text{ A}/\mu\text{s}$	1	μs
t_{gr}	$V_D = 0,67 * V_{DRM}$	2	μs
$(di/dt)_{cr}$	$T_{vj} = 130 \text{ }^{\circ}\text{C}$	max. 250	A/μs
$(dv/dt)_{cr}$	$T_{vj} = 130 \text{ }^{\circ}\text{C}$	max. 1000	V/μs
t_q	$T_{vj} = 130 \text{ }^{\circ}\text{C}$	50 ... 150	μs
I_H	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; typ. / max.	150 / 500	mA
I_L	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; $R_G = 33 \text{ }^{\circ}\Omega$; typ. / max.	300 / 2000	mA
V_{GT}	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; d.c.	min. 3	V
I_{GT}	$T_{vj} = 25 \text{ }^{\circ}\text{C}$; d.c.	min. 200	mA
V_{GD}	$T_{vj} = 130 \text{ }^{\circ}\text{C}$; d.c.	max. 0,25	V
I_{GD}	$T_{vj} = 130 \text{ }^{\circ}\text{C}$; d.c.	max. 10	mA
$R_{th(j-c)}$	cont.; per thyristor / per module	0,11 / 0,055	K/W
$R_{th(j-c)}$	sin. 180; per thyristor / per module	0,116 / 0,058	K/W
$R_{th(j-c)}$	rec. 120; per thyristor / per module	0,13 / 0,065	K/W
$R_{th(c-s)}$	per thyristor / per module	0,04 / 0,02	K/W
T_{vj}		- 40 ... + 130	$^{\circ}\text{C}$
T_{stg}		- 40 ... + 130	$^{\circ}\text{C}$
V_{isol}	a. c. 50 Hz; r.m.s.; 1 s / 1 min.	3600 / 3000	V~
M_s	to heatsink	5 ± 15 % ²⁾	Nm
M_t	to terminals	9 ± 15 % ³⁾	Nm
a		5 * 9,81	m/s ²
m	approx.	750	g
Case	SKKT SKKH	A 73a A 76a	









SKKT






SKKH



SKKT 330, SKKH 330



SKKT 330, SKKH 330



This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.