




Single Phase SSR (240VAC)
10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Triac output


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W B = 1.0°C/W
C & D = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • TTL/CMOS Compatible (Sink mode) • Output : NO/NC Configuration • Safety cover provision • Built-In Snubber • Chassis Mountable/DIN Mountable with Integral heatsink • Reverse Voltage Protection

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 JDA 331000	001 JDA 331600	001 JDA 332500	001 JDA 334000
Control Volt Range		Vdc	3-32	3-32	3-32	3-32
Control Curr Range		m A	1-20	1-20	1-20	1-20
Pick-Up Voltage		Vdc	3.0	3.0	3.0	3.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance		K ohms	1.8	1.8	1.8	1.8
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	24-330	24-330	24-330	24-330
Rep Peak Off State Voltage	V _{drrm}	Vpk	600	600	600	600
Off State Leakage Curr	I _{drrm}	mA	10	10	10	10
Zero T-On Voltage		Vpk	25	25	25	25
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	300
Holding Current	I _H	m A	75	75	150	150
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.4	2.5	1.5	1.2
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn -Off	T- Off	ms	10	10	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A ² S	50	120	300	400

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 J/K

Input

Output


Single Phase SSR (240VAC)
10 ~ 40 Amps

INPUT : AC Control
OUTPUT : Triac output


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W B = 1.0°C/W
C & D = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Output : NO/NC Configuration • Safety cover provision • Built-In Snubber • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 JAA 331028	001 JAA 331628	001 JAA 332528	001 JAA 334028
Control Volt Range		Vac	90 ~ 280	90 ~ 280	90 ~ 280	90 ~ 280
Control Curr Range		m A	9 ~ 18	9 ~ 18	9 ~ 18	9 ~ 18
Pick-Up Voltage		Vac	90	90	90	90
Drop-Out Voltage		Vac	45	45	45	45
Input Resistance		K Ohms	33	33	33	33
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	24-330	24-330	24-330	24-330
Rep Peak Off State Voltage	V _{drm}	Vpk	600	600	600	600
Off State Leakage Curr	I _{drm}	mA	10	10	10	10
Zero T-On Voltage		Vpk	25	25	25	25
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	300
Holding Current	I _H	m A	75	75	150	150
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.4	2.5	1.5	1.2
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40	40
Turn -Off	T- Off	ms	80	80	80	80
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A²S	50	120	300	400

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 J/K

Input

Output

Single Phase SSR (440VAC)
10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Triac output


ERI®




Series : 001 J/K




Schematic



Mechanical Drawing



Derating Curve



Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Comptible (Sink mode) • Output : NO/NC Configuration • Safety cover provision
- Built-In Snubber • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 JDA 481000	001 JDA 481600	001 JDA 482500	001 JDA 484000
Control Volt Range		Vdc	3-32	3-32	3-32	3-32
Control Curr Range		m A	1-25	1-25	1-25	1-25
Pick-Up Voltage		Vdc	3.0	3.0	3.0	3.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	Vrms	Vac	48-480	48-480	48-480	48-480
Rep Peak Off State Voltage	Vdrms	Vpk	800	800	800	800
Off State Leakage Curr	Idrms	mA	10	10	10	10
Zero T-On Voltage		Vpk	25	25	25	25
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr (Non Rep)	I _{TSM}	A	100	160	250	300
Holding Current	I _H	m A	75	75	150	150
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.4	2.5	1.5	1.2
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn-Off	T-Off	ms	10	10	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A ² S	50	120	300	400

*Our policy is one of continuous development and specifications are subject to change without notice. warranty is limited to a period of one year for relay value only


Input

Output


Single Phase SSR (440VAC)
10 ~ 40 Amps

INPUT : AC Control,
OUTPUT : Triac output


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W B = 1.0°C/W
C & D = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Output : NO/NC Configuration
- Safety cover provision • Built-In Snubber • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 JAA 481028	001 JAA 481628	001 JAA 482528	001 JAA 484028
Control Volt Range		Vac	90-280	90-280	90-280	90-280
Control Curr Range		m A	9-18	9-18	9-18	9-18
Pick-Up Voltage		Vac	90	90	90	90
Drop-Out Voltage		Vac	45	45	45	45
Input Resistance		K Ohms	20	20	20	20
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	48-480	48-480	48-480	48-480
Rep Peak Off State Voltage	V _{drm}	Vpk	800	800	800	800
Off State Leakage Curr	I _{drm}	mA	10	10	10	10
Zero T-On Voltage		VpK	25	25	25	25
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	300
Holding Current	I _H	m A	75	75	150	150
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.4	2.5	1.5	1.2
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40	40
Turn -Off	T- Off	ms	80	80	80	80
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A²S	50	120	300	400

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 J/K

Input

Output


Single Phase SSR (240VAC)
10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W B = 1.0°C/W
C & D = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Compatible (Sink mode) • Output : NO/NC Configuration • Suitable for inductive loads
- Built-In Snubber • Safety cover provision • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 SJDA 331000	001 SJDA 331600	001 SJDA 332500	001 SJDA 334000
Control Volt Range		Vdc	3-32	3-32	3-32	3-32
Control Curr Range		m A	1-25	1-25	1-25	1-25
Pick-Up Voltage		Vdc	3.0	3.0	3.0	3.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	24-330	24-330	24-330	24-330
Peak Off State Voltage	V _{drm}	Vpk	600	600	600	600
Off State Leakage Curr	I _{drm}	mA	10	10	10	10
Zero T-On Voltage		Vpk	20	20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.6	1.6
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	400
Holding Current	I _H	m A	50	70	120	250
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	500	500	500
Thermal Resistance	R _{TH}	°C/W	2.0	1.6	1.0	0.88
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn -Off	T- Off	ms	10	10	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A ² S	50	128	220	560

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 SJ/K


Input

Output


Single Phase SSR (240VAC)
10 ~ 40 Amps

INPUT : AC Control,
OUTPUT : Back-to-Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W B = 1.0°C/W
C & D = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC
- Zero Voltage Turn On/Random Turn On
- Output : NO/NC Configuration
- Suitable for inductive loads
- Built-In Snubber
- Safety cover provision
- Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 SJAA 331028	001 SJAA 331628	001 SJAA 332528	001 SJAA 334028
Control Volt Range		Vac	90-280	90-280	90-280	90-280
Control Curr Range		m A	9-18	9-18	9-18	9-18
Pick-Up Voltage		Vac	90	90	90	90
Drop-Out Voltage		Vac	45	45	45	45
Input Resistance		K Ohms	13(Typ)	13(Typ)	13(Typ)	13(Typ)
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	24-330	24-330	24-330	24-330
Peak Off State Voltage	V _{drm}	Vpk	600	600	600	600
Off State Leakage Curr	I _{drm}	mA	10	10	10	10
Zero T-On Voltage		Vpk	20	20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.6	1.6
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	400
Holding Current	I _H	m A	50	70	120	250
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	500	500	500
Thermal Resistance	R _{TH}	°C/W	2.0	1.6	1.0	0.88
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40	40
Turn -Off	T- Off	ms	80	80	80	80
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A²S	50	128	220	560

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 SJ/K

Input

Output


Single Phase SSR (440VAC)
10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W B = 1.0°C/W
C & D = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Compatible (Sink mode) • Output : NO/NC Configuration • Suitable for inductive loads
- Built-In Snubber • Safety cover provision • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 SJDA 481000	001 SJDA 481600	001 SJDA 482500	001 SJDA 484000
Control Volt Range		Vdc	3-32	3-32	3-32	3-32
Control Curr Range		m A	1-25	1-25	1-25	1-25
Pick-Up Voltage		Vdc	3.0	3.0	3.0	3.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance		kohms	Current Regulator	Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	Vrms	Vac	48-480	48-480	48-480	48-480
Peak Off State Voltage	Vdrms	Vpk	800	800	800	800
Off State Leakage Curr	Idrms	mA	10	10	10	10
Zero T-On Voltage		Vpk	20	20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.6	1.6
Peak one Cycle Surge Curr (Non Rep)	I _{TSM}	A	100	160	250	400
Holding Current	I _H	m A	50	70	120	250
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	500	500	500
Thermal Resistance	R _{TH}	°C/W	2.0	1.6	1.0	0.88
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn-Off	T-Off	ms	10	10	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A ² S	50	128	220	560

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 SJ/K


Input

Output


Single Phase SSR (440VAC)
10 ~ 40 Amps

INPUT : AC Control,
OUTPUT : Back-to-Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Output : NO/NC Configuration • Suitable for inductive loads • Built-In Snubber • Safety cover provision • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 SJAA 481028	001 SJAA 481628	001 SJAA 482528	001 SJAA 484028
Control Volt Range		Vac	90-280	90-280	90-280	90-280
Control Curr Range		m A	9-18	9-18	9-18	9-18
Pick-Up Voltage		Vac	90	90	90	90
Drop-Out Voltage		Vac	45	45	45	45
Input Resistance		kohms	13(typ)	13(typ)	13(typ)	13(typ)
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	48-480	48-480	48-480	48-480
Peak Off State Voltage	V _{drm}	Vpk	800	800	800	800
Off State Leakage Curr	I _{drm}	mA	10	10	10	10
Zero T-On Voltage		Vpk	35	35	35	35
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.6	1.6
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	500	500
Holding Current	I _H	m A	50	70	120	250
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	500	500	500
Thermal Resistance	R _{TH}	°C/W	2.0	1.6	1.0	0.88
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40	40
Turn-Off	T-Off	ms	80	80	80	80
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A²S	50	128	220	560

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 SJ/K

Input

Output

Single Phase SSR (240VAC)
10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Triac output


ERI®




Series : 018 JK




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W B = 1.0°C/W
C & D = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • TTL/CMOS Compatible (Sink mode) • Output : NO/NC Configuration • Safety cover provision • Built-In Snubber • Chassis Mountable/DIN Mountable with Integral heatsink • Reverse Voltage Protection

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	018 JDA 331000	018 JDA 331600	018 JDA 332500	018 JDA 334000
Control Volt Range		Vdc	3-32	3-32	3-32	3-32
Control Curr Range		m A	1-20	1-20	1-20	1-20
Pick-Up Voltage		Vdc	3.0	3.0	3.0	3.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance		K ohms	1.8	1.8	1.8	1.8
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	Vrms	Vac	24-480	24-480	24-480	24-480
Rep Peak Off State Voltage	Vdrms	Vpk	600~800	600~800	600~800	600~800
Off State Leakage Curr	Idrm	mA	10	10	10	10
Zero T-On Voltage		Vpk	25	25	25	25
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	300
Holding Current	I _H	m A	75	75	150	150
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.4	2.5	1.5	1.2
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn -Off	T- Off	ms	10	10	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A ² S	50	120	300	400

Input

Output


Single Phase SSR (660VAC)
50 ~ 90 Amps

INPUT : DC Control,
OUTPUT : Direct Copper Bonded Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



$$F = 0.14^{\circ}\text{C/W}$$

For Heatsink details refer to "Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Compatible (Sink mode)
- Output : NO Configuration • Safety cover provision • Built-In Snubber • Higher load cycle resistance • High thermal cycling capacity
- High Fusing current • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KD' in place of 'D'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS		
Parameter	Symbol	Unit	020 D 125000	020 D 127500	020 D 129000
Control Volt Range	V _{dc}		4-32	4-32	4-32
Control Curr Range	m A		8-35	8-35	8-35
Pick-Up Voltage	V _{dc}		4.0	4.0	4.0
Drop-Out Voltage	V _{dc}		1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	50	75	90
Mains Control Volt	V _{rms}	Vac	48-660	48-660	48-660
Peak Off State Voltage	V _{drm}	V _{pk}	1200	1200	1200
Off State Leakage Curr	I _{drm}	mA	5	5	5
Zero T-On Voltage	V _{pk}		20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	2.0	2.0
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	500	1150	1350
Holding Current	I _H	m A	300	300	300
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	1000	1000	1000
Thermal Resistance	R _{TH}	°C/W	0.7	0.6	0.3
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10
Turn-Off	T-Off	ms	10	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80	-30 to +80
Fusing Current	I _T ²	A ² S	1250	5000	5000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 020 D/KD

Input

Output

Single Phase SSR (660VAC)
125 ~ 205 Amps

INPUT : DC Control,
OUTPUT : Direct Copper Bonded Back - to - Back SCR


ERI®




Series : 020 D/KD




Schematic



Mechanical Drawing



Derating Curve



Heatsink $R_{th} = 0.14^{\circ}\text{C/W}$
with cooling fan of 70CFM for 125A &
100CFM for 150-205A

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Compatible (Sink mode)
- Output : NO Configuration • Safety cover provision • Built-In Snubber • Higher load cycle resistance • High thermal cycling Capacity
- High Fusing current • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ $T_A = 25^{\circ}\text{C}$

Note: For Random T - On SSR, add letter 'KD' in place of 'D'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	020 D 1212500	020 D 1215000	020 D 1217500	020 D 1220500
Control Volt Range		Vdc	4-32	4-32	4-32	4-32
Control Curr Range		m A	8-35	8-35	8-35	8-35
Pick-Up Voltage		Vdc	4.0	4.0	4.0	4.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	125	150	175	205
Mains Control Volt	Vrms	Vac	48-660	48-660	48-660	48-660
Peak Off State Voltage	Vdrms	Vpk	1200	1200	1200	1200
Off State Leakage Curr	Idrms	mA	5	5	5	5
Zero T-On Voltage		Vpk	20	20	20	20
On state Voltage Drop	V_{TM}	Vac	2.0	2.0	2.0	2.0
Peak one Cycle Surge Curr(Non Rep)	I_{TSM}	A	1350	1350	1500	2250
Holding Current	I_H	m A	300	500	500	500
Critical Rate of Rise of Off State Voltage	dv/dt	V/ μ s	1000	1000	1000	1000
Thermal Resistance	R_{TH}	$^{\circ}\text{C/W}$	0.35	0.35	0.25	0.1
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn-Off	T-Off	ms	10	10	10	10
Operating Temp	T Oper	$^{\circ}\text{C}$	-25 to +80	-25 to +80	-25 to +80	-25 to +80
Fusing Current	I_T^2	A ² S	5000	8000	15000	25000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Input

Output


Single Phase SSR (660VAC)
50 ~ 90 Amps

INPUT : AC Control,
OUTPUT : Direct Copper Bonded Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



$$F = 0.14^{\circ}\text{C/W}$$

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Output : NO Configuration • Safety cover provision • Built-In Snubber • Higher load cycle resistance • High thermal cycling Capacity • High Fusing current
- Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KA' in place of 'A'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS		
Parameter	Symbol	Unit	020 A 125028	020 A 127528	020 A 129028
Control Volt Range		Vac	90-280	90-280	90-280
Control Curr Range		m A	9-18	9-18	9-18
Pick-Up Voltage		Vac	90	90	90
Drop-Out Voltage		Vac	45	45	45
Input Resistance		K Ohms	20.0(Typ)	20.0(Typ)	20.0(Typ)
Rms On State Current	I_T	A	50	75	90
Mains Control Volt	V _{rms}	Vac	48-660	48-660	48-660
Peak Off State Voltage	V _{drm}	Vpk	1200	1200	1200
Off State Leakage Curr	I _{drm}	mA	5	5	5
Zero T-On Voltage		Vpk	20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	2.0	2.0
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	500	1150	1350
Holding Current	I _H	m A	300	300	300
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	1000	1000	1000
Thermal Resistance	R _{TH}	°C/W	0.7	0.6	0.3
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40
Turn-Off	T-Off	ms	80	80	80
Operating Temp	T Oper	°C	-25 to +80	-25 to +80	-25 to +80
Fusing Current	I _T ²	A²S	1250	5000	5000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 020 A/KA

Input

Output


Single Phase SSR (660VAC)
125 ~ 205 Amps

INPUT : AC Control,
OUTPUT : Direct Copper Bonded Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



Heatsink $R_{th} = 0.14^{\circ}\text{C/W}$
with cooling fan of 70CFM for 125A &
100CFM for 150-205A

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Output : NO Configuration • Safety cover provision • Built-In Snubber • Higher load cycle resistance • High thermal cycling Capacity • High Fusing current. • Chassis Mountable / DIN Mountable with Integral heatsink.

Electrical Specification @ $T_A = 25^{\circ}\text{C}$

Note: For Random T - On SSR, add letter 'KA' in place of 'A'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	020 A 1212528	020 A 1215028	020 A 1217528	020 A 1220528
Control Volt Range		Vac	90-280	90-280	90-280	90-280
Control Curr Range		m A	9-18	9-18	9-18	9-18
Pick-Up Voltage		Vac	90	90	90	90
Drop-Out Voltage		Vac	45	45	45	45
Input Resistance		K Ohms	20.0(Typ)	20.0(Typ)	20.0(Typ)	20.0(Typ)
Rms On State Current	I_T	A	125	150	175	205
Mains Control Volt	V_{rms}	Vac	48-660	48-660	48-660	48-660
Peak Off State Voltage	V_{drm}	Vpk	1200	1200	1200	1200
Off State Leakage Curr	I_{drm}	mA	5	5	5	5
Zero T-On Voltage			20	20	20	20
On state Voltage Drop	V_{TM}	Vac	2.0	2.0	2.0	2.0
Peak one Cycle Surge Curr(Non Rep)	I_{TSM}	A	1350	1350	1500	2250
Holding Current	I_H	m A	300	500	500	500
Critical Rate of Rise of Off State Voltage	dv/dt	V/ μs	1000	1000	1000	1000
Thermal Resistance	R_{TH}	$^{\circ}\text{C/W}$	0.35	0.35	0.25	0.1
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40	40
Turn -Off	T- Off	ms	80	80	80	80
Operating Temp	T Oper	$^{\circ}\text{C}$	-25 to +80	-25 to +80	-25 to +80	-25 to +80
Fusing Current	I_T^2	A ² S	5000	8000	15000	25000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 020 A/KA

Input

Output


Single Phase SSR (240VAC)
2 Amps

INPUT : DC Control,
OUTPUT : Triac


ERI®




Series : 002 J/K




Schematic



Mechanical Drawing



Derating Curve



Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Comptible (Sink mode) • Output : NO/NC Configuration • Built-In Snubber • PCB Mountable
- Pins are polarised

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS
Parameter	Symbol	Unit	002 JDA 330200
Control Volt Range		Vdc	3-32
Control Curr Range		m A	1-30
Pick-Up Voltage		Vdc	3.0
Drop-Out Voltage		Vdc	1.0
Input Resistance		K Ohms	Current Regulator
Rms On State Current	I_T	A	2.0
Mains Control Volt	Vrms	Vac	24-330
Non-Rep Peak Off State Voltage	Vdrm	Vpk	600
Off State Leakage Curr	Idrm	mA	10
Zero T-On Voltage		Vpk	25
On state Voltage Drop	V_{TM}	Vac	1.6
Peak one Cycle Surge Curr(Non Rep)	I_{TSM}	A	100
Holding Current	I_H	mA	75
Critical Rate of Rise of Off State Voltage	dv/dt	V/ μ s	200
Thermal Resistance	R_{TH}	°C/W	2.0
Frequency Range	f	Hz	47 ~ 63
Turn-On	T-On	ms	10
Turn -Off	T-Off	ms	10
Operating Temp	T Oper	°C	-30 to +80
Fusing Current	I_T^2	A²S	50

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.


Input

Output


Single Phase SSR (240VAC)
2 ~ 7 Amps

INPUT : DC Control,
OUTPUT : Triac


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W
For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Comptible (Sink mode) • PCB Mountable • Chassis Mountable.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS	
Parameter	Symbol	Unit	006 JDA 330205	006 JDA 330705
Control Volt Range		Vdc	5/12/24	5/12/24
Control Curr Range		m A	10	10
Pick-Up Voltage		Vdc	5/12/24	5/12/24
Drop-Out Voltage		Vdc	1/3/5	1/3/5
Input Resistance		K Ohms	0.5/1.2/2.2	0.5/1.2/2.2
Rms On State Current	I_T	A	2.0	7.0
Mains Control Volt	Vrms	Vac	24-330	24-330
Non-Rep Peak Off State Voltage	Vdrms	Vpk	600	600
Off State Leakage Curr	Idrm	μA	100	100
Zero T-On Voltage		Vpk	25	25
On state Voltage Drop	V _{TM}	Vac	1.6	1.6
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	100
Holding Current	I _H	mA	75	75
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200
Thermal Resistance	R _{TH}	°C/W	1.6	1.6
Frequency Range	f	Hz	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10
Turn -Off	T-Off	ms	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80
Fusing Current	I _T ²	A ² S	50	50

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 006 J/K

Input

Output


Single Phase SSR (240VAC)
2 ~ 4 Amps

INPUT : DC Control,
OUTPUT : Triac


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W
For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Comptible (Sink mode) • PCB Mountable • Compatible to Std IC base(008/010 Series only).

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS	
Parameter	Symbol	Unit	004 JDA 330405	008 JDA 330205
Control Volt Range		Vdc	5/12/24	5/12/24
Control Curr Range		m A	5-15	5-15
Pick-Up Voltage		Vdc	5/12/24	5/12/24
Drop-Out Voltage		Vdc	1/3/5	1/3/5
Input Resistance		K Ohms	0.5 - 2.0(Typ)	0.5 - 2.0(Typ)
Rms On State Current	I_T	A	4.0	2.0
Mains Control Volt	Vrms	Vac	24-330	24-330
State Voltage	Vdrms	Vpk	600	600
Off State Leakage Curr	Idrms	mA	10	10
Zero T-On Voltage		Vpk	25	25
On state Voltage Drop	V _{TM}	Vac	1.6	1.6
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	100
Holding Current	I _H	m A	75	75
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200
Thermal Resistance	R _{TH}	°C/W	1.0	0.88
Frequency Range	f	Hz	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10
Turn-Off	T-Off	ms	10	10
Operating Temp	T Oper	°C	-30 to +80	-30 to +80
Fusing Current	I ² _T	A²S	50	50

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 004/008 J/K


Input

Output


Single Phase SSR (240VAC)
3 Amps

INPUT : DC Control,
OUTPUT : Triac


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2°C/W
For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Zero Voltage Turn On/Random Turn On • Reverse Voltage Protection; TTL/CMOS Comptible (Sink mode) • PCB Mountable • Compatible to Std IC base(008/010 Series only).

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS
Parameter	Symbol	Unit	010 JDA 330305
Control Volt Range		Vdc	5/12/24
Control Curr Range		m A	5-15
Pick-Up Voltage		Vdc	5/12/24
Drop-Out Voltage		Vdc	1/3/5
Input Resistance		K Ohms	0.5 - 2.0(Typ)
Rms On State Current	I_T	A	3.0
Mains Control Volt	Vrms	Vac	24-330
State Voltage	Vdrms	Vpk	600
Off State Leakage Curr	Idrms	mA	10
Zero T-On Voltage		Vpk	25
On state Voltage Drop	V _{TM}	Vac	1.6
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100
Holding Current	I _H	m A	75
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200
Thermal Resistance	R _{TH}	°C/W	0 . 88
Frequency Range	f	Hz	47 ~ 63
Turn-On	T-On	ms	10
Turn-Off	T-Off	ms	10
Operating Temp	T Oper	°C	-30 to +80
Fusing Current	I _T ²	A²S	50

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 010 J/K

Input


Output

Three Phase SSR (480VAC)
10 ~ 40 Amps


INPUT : DC Control,
OUTPUT : Triac




Schematic



Mechanical Drawing



Derating Curve



C & D = 0.5°C/W
F & G = 0.14°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Voltage Range 50 to 480 Vac
- Load Current 3x10A/16A/25A/40A • Reverse Polarity Protection

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	012 JDA 481000	012 JDA 481600	012 JDA 482500	012 JDA 484000
Control Volt Range		Vdc	3-32	3-32	3-32	3-32
Control Curr Range		m A	80	80	80	80
Pick-Up Voltage		Vdc	3.0	3.0	3.0	3.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	50-480	50-480	50-480	50-480
Peak Off State Voltage	V _{drm}	Vpk	800 ~ 1200	800 ~ 1200	800 ~ 1200	800 ~ 1200
Off State Leakage Curr	I _{drm}	mA	10	10	10	10
Zero T-On Voltage		Vpk	20	20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	350
Holding Current	I _H	mA	150	150	250	250
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.5	2.5	1.5	1.0
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn-Off	T-Off	ms	10	10	10	10
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Fusing Current	I _T ²	A²S	50	120	260	610

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 012 J/K

Input

Output


Three Phase SSR (480VAC)
50 ~ 90 Amps

INPUT : DC Control,
OUTPUT : Direct Copper Bonded Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



$$F = 0.14^{\circ}\text{C/W}$$

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Voltage Range 50 to 480 Vac • Load Current 3x50A/75A/90A
- Reverse Polarity Protection for DC Input Control.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS		
Parameter	Symbol	Unit	012 SJDA 485000	012 SJDA 487500	012 SJDA 489000
Control Volt Range		Vdc	4-32	4-32	4-32
Control Curr Range		m A	8-80	8-80	8-80
Pick-Up Voltage		Vdc	4.0	4.0	4.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	50	75	90
Mains Control Volt	Vrms	Vac	50-480	50-480	50-480
Peak Off State Voltage	Vdrms	Vpk	800 ~ 1200	800 ~ 1200	800 ~ 1200
Off State Leakage Curr	Idrm	mA	10	10	10
Zero T-On Voltage		Vpk	20	20	20
On state Voltage Drop	V _{TM}	Vac	2	2	2
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	500	1150	1150
Holding Current	I _H	m A	250	300	300
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	1000	1000	1000
Thermal Resistance	R _{TH}	°C/W	0.7	0.6	0.3
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10
Turn-Off	T-Off	ms	10	10	10
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80
Fusing Current	I _T ²	A ² S	1250	5000	5000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 012 SJ/K

Input


Output

Three Phase SSR (480VAC)
10 ~ 40 Amps


INPUT : AC Control,
OUTPUT : Triac




Schematic



Mechanical Drawing



Derating Curve



C & D = 0.5°C/W
F & G = 0.14°C/W

For Heatsink details refer to "Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC
- Voltage Range 50 to 480 Vac
- Load Current 3x10A/16A/25A/40A

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	012 JAA 481028	012 JAA 481628	012 JAA 482528	012 JAA 484028
Control Volt Range		Vac	90-280	90-280	90-280	90-280
Control Curr Range		m A	8-80	8-80	8-80	8-80
Pick-Up Voltage		Vac	90	90	90	90
Drop-Out Voltage		Vac	45	45	45	45
Input Resistance		K Ohms	13.0(Typ)	13.0(Typ)	13.0(Typ)	13.0(Typ)
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	V _{rms}	Vac	50-480	50-480	50-480	50-480
Peak Off State Voltage	V _{drm}	Vpk	800 ~ 1200	800 ~ 1200	800 ~ 1200	800 ~ 1200
Off State Leakage Curr	I _{drm}	mA	10	10	10	10
Zero T-On Voltage		Vpk	20	20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	100	160	250	350
Holding Current	I _H	mA	250	250	200	200
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.5	2.5	1.5	1.0
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40	40
Turn-Off	T-Off	ms	80	80	80	80
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Fusing Current	I _T ²	A²S	50	120	260	610

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 012 J/K

Input

Output


Three Phase SSR (480VAC)
50 ~ 90 Amps

INPUT : AC Control,
OUTPUT : Direct Copper bonded Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



$$F = 0.14^{\circ}\text{C/W}$$

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC
- Voltage Range 50 to 480 Vac
- Load Current 3x50A/75A/90A

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS		
Parameter	Symbol	Unit	012 SJAA 485028	012 SJAA 487528	012 SJAA 489028
Control Volt Range		Vac	90-280	90-280	90-280
Control Curr Range		m A	8-80	8-80	8-80
Pick-Up Voltage		Vac	90	90	90
Drop-Out Voltage		Vac	45	45	45
Input Resistance		K Ohms	13.0(Typ)	13.0(Typ)	13.0(Typ)
Rms On State Current	I_T	A	50	75	90
Mains Control Volt	Vrms	Vac	50-480	50-480	50-480
Peak Off State Voltage	Vdrms	Vpk	800 ~ 1200	800 ~ 1200	800 ~ 1200
Off State Leakage Curr	Idrms	mA	10	10	10
Zero T-On Voltage		Vpk	35	35	35
On state Voltage Drop	V _{TM}	Vac	2	2	2
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	500	1150	1150
Holding Current	I _H	m A	250	300	300
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	1000	1000	1000
Thermal Resistance	R _{TH}	°C/W	0.7	0.6	0.3
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	40	40	40
Turn - Off	T- Off	ms	80	80	80
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80
Fusing Current	I _T ²	A ² S	1250	5000	5000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.


Three Phase Motor Reversing SSR (480VAC) 10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Triac


ERI®




Schematic



Mechanical Drawing



Derating Curve



C & D = 0.5°C/W
F & G = 0.14°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Voltage Range 50 to 480 Vac • Load Current 2x10A/16A/25A/40A
- Reverse Polarity Protection for DC Input Control • Interlocking Protection included.

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'K' in place of 'J'.


ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	012 RJDA 481000	012 RJDA 481600	012 RJDA 482500	012 RJDA 484000
Control Volt Range	Vdc		4-32	4-32	4-32	4-32
Control Curr Range		m A	80	80	80	80
Pick-Up Voltage	Vdc		4.0	4.0	4.0	4.0
Drop-Out Voltage		mA	1.0	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I_T	A	10	16	25	40
Mains Control Volt	Vrms	Vac	50-480	50-480	50-480	50-480
Peak Off State Voltage	Vdrm	Vpk	800 ~ 1200	800 ~ 1200	800 ~ 1200	800 ~ 1200
Off State Leakage Curr	Idrm	mA	10	10	10	10
Zero T-On Voltage	Vpk		20	20	20	20
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr (Non Rep)	I _{TSM}	A	100	160	250	350
Holding Current	I _H	m A	100	100	250	250
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	250
Thermal Resistance	R _{TH}	°C/W	3.5	2.5	1.5	1.0
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn-Off	T-Off	ms	10	10	10	10
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Fusing Current	I _T ²	A²S	50	120	260	560

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.


Series : 012 RJ/K

Input

Output




Schematic



1 & 2 AC Input, 3 Logic Supply,
4 Output, 5 Common

Mechanical Drawing




Highlights


- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package with hold-down screw
- PCB Mountable
- Pins are polarised

Electrical Specification @ TA = 25°C


ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS	
		104 AI 032528	
Parameter	Units	Min	Max
Input On Voltage	V(RMS)	180	280
Input Off Voltage	V(RMS)	0.0	15
Allowable Input Current for Output Off-State	mA(RMS)	0.0	0.25
Input Current at 240 VRMS	mA(RMS)		3.0
Frequency range	Hz	47	63
Input Impedence	K Ohms	64	96
Over Voltage	Vpk		600
Isolation Voltage	V(RMS)	2500	
<i>Note : All voltages referenced to Pin 5</i>			
Breakdown voltage (Pin 5)	VDC	30	
Output Current (Pin 4)	mA		25
On-State Voltage (Pin 4) (at 25 mADC)	VDC		0.4
Off-State Leakage (Pin 4) (at 30 VDC)	μA		100
Logic supply voltage (Pin 3)	VDC	3.5	6.0
Logic supply Current (Pin 3) No External LED	mA		8.0
Logic supply Current with External LED	mA		5.5
Turn-On Time	mS		20
Turn-Off Time	mS		20
Operating Temperature	°C	-30	80



Schematic



Mechanical Drawing



Highlights

- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package with hold-down screw
- PCB Mountable
- Pins are polarised

Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS	
		104 DI 032505	
Parameter	Units	Min	Max
Input On Voltage	VDC	3.0	32
Input Off Voltage	VDC	0.0	1.0
Allowable Input Current for Output Off-State	mA	0.0	0.25
Input Current at 5 VDC	mA	2	4.0
Frequency range	-	-	-
Input Resistance	Ohms	0.85	1.86
Isolation Voltage	V(RMS)	2500	
<i>Note : All voltages referenced to Pin 5</i>			


Breakdown voltage (Pin 5)	VDC	30	
Output Current (Pinn 4)	mA		25
On-State Voltage (Pin 4) (at 25 mADC)	VDC		0.4
Off-State Leakage (Pin 4) (at 30 VDC)	μA		100
Logic supply voltage (Pin 3)	VDC	3.5	6.0
Logic supply Current (Pin 3) No External LED	mA		8.0
Logic supply Current with External LED	mA		5.5
Turn-On Time	mS		5
Turn-Off Time	mS		5
Operating Temperature	°C	-30	80

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.




AC O/P


Schematic



Mechanical Drawing



Derating Curve



Highlights

- Compatible to TTL and CMOS logic
- Zero Voltage or Random turn on
- LED indication
- PCB Mountable
- Pins are polarised
- Industrial standard package with hold-down screw


Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS	
104 AO 240305			
Parameter	Units	Min	Max
Input On Voltage	VDC	3.0	8.0
Input Off Voltage	VDC	-8.0	1.0
Input Current at 5 VDC	mA		10
Input Resistance	Ohms	445	815
Isolation Voltage	V(RMS)	2500	
Load Current at 45°C	A(RMS)	0.05	3.0
Load Voltage	V(RMS)	24	280
Frequency Range	Hz	47	63
Surge Current Non-repetive (1 cycle)	Apk		80
Transient over-voltage	Vpk		600
On- state Voltage @ Rated Current	VRMS	1.5	
Off-State Leakage @ 240 VRMS	mA(RMS)		5
Off-State dv/dt	V/μs	200	
Turn-On Time (Next Zero Voltage	Cycle		1/2
Turn-Off Time (Next Zero current)	Cycle		1/2
Operating Temperature	°C	-30	80


**Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.*




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Compatible to TTL • Compatible to CMOS logic (optional) • LED indication • PCB Mountable • Pins are polarised • Industrial standard package with hold down screw


Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS	
		104 DO 060300	
Parameter	Units	Min	Max
Input On Voltage	VDC	3.0	32
Input Off Voltage	VDC	-8.0	1.0
Input Current at 5 VDC	mA		13
Input Resistance	Ohms	270	580
Isolation Voltage	V(RMS)	2500	
Load Current at 45°C	A(RMS)	0.05	3.0
Load Voltage	VDC	3.0	60
Surge Current(1Sec)		5.0	A
Transient over-voltage	Vpk		600
On-State Voltage @ Rated Current	VDC		1.5
Off-State Leakage @ 60 VDC	mA		1
Turn-On Time	μS		200
Turn-Off Time	μS		750
Operating Temperature	°C	-30	80




JDA241000


Schematic



Mechanical Drawing



Derating Curve



Highlights


- Compatible to TTL logic
- Built in zero cross circuit
- Low profile module
- High Repetitive off state voltage
- Pins are polarised

Electrical Specification @ TA = 25°C


ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS			
		106 AO 240300		106 AO 480300	
Parameter	Units	Min	Max	Min	Max
Input On Voltage	VDC	3	32	3	32
Input Off Voltage	VDC	1	-	1	-
Input Current at 5 VDC	mA	-	12	-	12
Input Resistance	Curr. Reglr	Curr. Reglr	Curr. Reglr	Curr. Reglr	Curr. Reglr
Input Reverse voltage	VDC	32	1	32	1
Isolation Voltage	V(RMS)	-	4000	-	4000
Load Current at 45°C	A	0.05	3	0.05	3
Load Voltage	VRMS	24	330	24	480
Frequency Range	Hz	47	63	47	63
Surge Current None-repetive (1 cycle)	A	-	80	-	80
Transient over-voltage	Vpk	-	600	-	800
On- state Voltage @ Rated Current	VRMS	-	1.6	-	1.6
Off-State Leakage @ 240 VRMS	mA	-	5	-	5
Critical rate of rise of off state voltage (dv/dt)	V/μs	200		200	
Turn-On Time (Next Zero Voltage)	Cycle	-	1/2	-	1/2
Turn-Off Time (Next Zero current)	Cycle	-	1/2	-	1/2
Operating Temperature	°C	-30	80	-30	80




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Compatible to TTL logic
- Built in zero cross circuit
- Mini Module
- High Repetitive off state voltage
- Pins are polarised

Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS			
		109 AO 240205		001 JDA 331605	
Parameter	Units	Min	Max	Min	Max
Input On Voltage	VDC	4	6	4	6
Input Off Voltage	VDC	1	-	1	-
Input Current at 5 VDC	mA	-	30	-	30
Input Resistance	Ohms		130		130
Input Reverse voltage	VDC	-32	-	-32	-
Isolation Voltage	VRMS	-	4000	-	4000
Load Current at 45°C	A	0.05	2	-	16
Load Voltage	VRMS	24	330	24	330
Frequency Range	Hz	47	63	47	63
Surge Current Non-rep (1 cycle)	A	-	80	-	160
Transient over-voltage	Vpk	-	600	-	600
On- state Voltage @ Rated Current	VRMS	-	1.6	-	1.6
Off-State Leakage @ 240 VRMS	mA	-	5	-	5
Critical rate of rise of off state voltage (dv/dt)	V/μs	200	-	200	-
Turn-On Time (Next Zero Voltage)	Cycle	-	1/2	-	10
Turn-Off Time (Next Zero current)	Cycle	-	1/2	-	10
Operating Temperature	°C	-30	80	-30	80


DC SSR
02 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Power Darlington/MOSFET

ERI®




Schematic




3 Input (+) & 4 Input (-)
1 & 2 Output

Mechanical Drawing



Derating Curve



A = 3.2°C/W
C = 0.5°C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Input Compatible to TTL logic • MOSFET OUTPUT • Reverse Polarity Protection. Chassis Mountable / DIN Rail Mountable with Integral heatsink.

Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	001 KDD 060500	001 KDD 201200	001 KDD 202500	001 KDD 204000
Control Volt Range		Vdc	3.5-32	3.5-32	3.5-32	3.5-32
Control Curr Range		mA	3.5	3.5	3.5	3.5
Pick-Up Voltage		Vdc	3.5	3.5	3.5	3.5
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator	Current Regulator
Load Current	I_T	A	2 ~ 5	12	25	40
Load Voltage		Vdc	60	200	200	200
Surge Curr (1 cycle Surge)			15	27	50	90
On state Voltage Drop	V _{TM}	Vdc	2	2.83	2.83	2.83
Off state leakage Current @ rated Voltage		mA	1	1	1	1
Turn-On	T-On	μs	500	600	600	600
Turn -Off	T-Off	μs	800	2600	2600	2600
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 001 K


Input

Output

DC SSR
2 Amps

INPUT : DC Control
OUTPUT : Power Darlington Transistor

ERI®




002K


006K




Schematic



Mechanical Drawing



Derating Curve



Salient Features

- Opto Isolation 2500 VAC • Input Compatible to TTL logic • Power Darlington Transistor • Reverse Polarity Protection • Chassis Mountable (006K).

Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS	
Parameter	Symbol	Unit	002 KDD 040205	006 KDD 040205
Control Volt Range		Vdc	3/5/12/24	3/5/12/24
Control Curr Range		m A	3 ~ 15	3 ~ 15
Pick-Up Voltage		Vdc	3/5/12/24	3.0
Drop-Out Voltage		Vdc	1/3/5	1/3/5
Input Resistance			Current Regulator	Current Regulator
Load Current	I_T	A	2	2
Load Voltage		Vdc	40	40
Surge Curr (1cycle Surge)			10	10
On state Voltage Drop	V _{TM}	Vdc	2	2
Off state leakage Current @ rated Voltage		mA	1	1
Turn-On	T-On	μs	500	500
Turn-Off	T-Off	μs	800	800
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.


Series : 002K & 006K

Input


Output




Schematic



Mechanical Drawing



Derating Curve



Heatsink of $R_{th} = 0.14^{\circ}\text{C/W}$

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Gets Protected against Load Short Circuits • Zero Voltage Turn On • Reverse Voltage Protection • TTL Compatible (Sink Mode) • Output No Configuration • Built-In Snubber • Chassis Mountable • Higher Load Cycle resistance • High Thermal Cycling Capacity • High Fusing Current.

Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	SCP 01 D 332500	SCP 01 D 335000	SCP 01 D 337500	SCP 01 D 339000
Control Volt Range		Vdc	6-30	6-30	6-30	6-30
Control Curr Range		m A	50	50	50	50
Pick-Up Voltage		Vdc	6.0	6.0	6.0	6.0
Drop-Out Voltage		Vdc	1.0	1.0	1.0	1.0
Input Resistance			Current Regulator	Current Regulator	Current Regulator	Current Regulator
Rms On State Current	I _T	A	25	50	75	90
Mains Control Volt		Vac	50-480	50-480	50-480	50-480
Peak Off State Voltage	V _{drM}	V _{pk}	600~800	600~800	600~800	600~800
Off State Lekage Curr	I _{drM}		10	10	10	10
Zero T-On Voltage		V _{pk}	25	25	25	25
On state Voltage Drop	V _{TM}	Vac	1.8	1.8	2.0	2.0
Peak one Cycle Surge Curr(Non Rep)	I _{TSM}	A	520	520	1150	1350
Holding Current	I _H	m A	300	300	300	300
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	1000	1000	1000	1000
Thermal Resistance	R _{TH}	°C/W	0.7	0.7	0.6	0.3
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn -Off	T- Off	ms	10	10	10	10
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Fusing Current	I _T ²	A ² S	1250	1250	5000	10000

**Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.*


Single Phase Power Proportional Controller (240VAC) 10 ~ 75 Amps

INPUT : DC Control,
OUTPUT : Triac/SCR Output


ERI®




Schematic



Mechanical Drawing



Derating Curve



A = 3.2 C/W B = 1.0 C/W
C & D = 0.5 C/W

For Heatsink details refer to
"Recommended Heatsink" chart

Salient Features

- Opto Isolation 2500 VAC • Input Control 0~10Vdc or 4~20mA • Built in Power Supply • Built-In Snubber
- Chassis Mountable

Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	012 PAC 241010	012 PAC 241610	012 PAC 242510	012 PAC 244010
Control Volt Range or		Vdc	0-10	0-10	0-10	0-10
Control Curr Range		m A	4 ~ 20	4 ~ 20	4 ~ 20	4 ~ 20

Rms On State Current	I _T	A	10	16	25	40
Mains Control Volt		Vac	200-240	200-240	200-240	200-240
Off state leakage Cur						
Rated Voltage			10	10	10	10
On state Voltage Drop	V _{TM}	Vac	1.6	1.6	1.85	1.85
Peak one Cycle Surge Curr (Non Rep)	I _{TSM}	A	100	160	250	300
Holding Current	I _H	m A	75	75	150	150
Critical Rate of Rise of Off State Voltage	dv/dt	V/μs	200	200	250	200
Thermal Resistance	R _{TH}	°C/W	3.4	2.5	1.5	1.2
Frequency Range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Turn-On	T-On	ms	10	10	10	10
Turn-Off	T-Off	ms	10	10	10	10
Operating Temp	T Oper	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Fusing Current	I _T ²	A²S	50	120	300	400

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : 012 PAC

Input

Output


Din Ready SSR (240 VAC)
10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Input: DC Control (TTL or CMOS Compatible) • Output: Back-to-Back SCR (No configuration) • Opto Isolation 2500VAC (4000 V optional) • Zero voltage turn-on or Random turn-on • Built-in safety cover • Reverse voltage protection
- Built in snubber for high DV/DT • DIN mount or back plate mounting • LED indicator showing relay 'ON' status

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KD' in place of 'D'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	DIN 30D 241000	DIN 30D 241600	DIN 30D 242500	DIN 30D 244000
Control voltage range		Vdc	3 - 32	3 - 32	3 - 32	3 - 32
Control current range		mA	8 - 30	8 - 30	8 - 30	8 - 30
Pick-up voltage		Vdc	3.0	3.0	3.0	3.0
Drop-out voltage		Vdc	1.0	1.0	1.0	1.0
Input resistance			Current regulator	Current regulator	Current regulator	Current regulator
RMS on-state current	IT	A	10	16	25	40
Mains control volt		Vac	24 - 240	24 - 240	24 - 240	24 - 240
Repetitive peak off state voltage	Vdrn	Vpk	600	600	600	600
Zero turn-on voltage		Vac	35	35	35	35
On-state voltage drop	Vtm	Vac	1 . 6	1 . 6	1 . 8	1 . 8
Off-state leakage current @ rated voltage	Idrm	mA	5	5	5	5
Peak one cycle surge Current (Non-Rrep)	ITSM	A	100	250	800	800
Holding current	IH	mA	75	120	250	250
Critical rate of rise of off state voltage	dv/dt	V/μs	200	250	500	500
Thermal resistance (junction to case)	Rthjc	°C/W	1.5	1.3	0.43	0.43
Frequency range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Storage temperature	Ts	°C	- 30 to + 100	- 30 to + 100	- 30 to + 100	- 30 to + 100
Operating temperature	To	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Turn-on time	T-on	ms	10	10	10	10
Turn-off time	T-off	ms	10	10	10	10
Fusing current	I ² _T	A ² S	72	128	3700	3700

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.


Din Ready SSR (240 VAC)
10 ~ 40 Amps

INPUT : AC Control,
OUTPUT : Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Input: AC Control • Output: Back-to-Back SCR (No configuration) • Opto Isolation 2500VAC (4000 V optional) • Zero voltage turn-on or Random turn-on • Built-in safety cover • Built-in snubber for high DV/DT • DIN mount or back plate mounting • LED indicator showing relay 'ON' status

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KA' in place of 'A'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	DIN 30A 241028	DIN 30A 241628	DIN 30A 242528	DIN 30A 244028
Control voltage range		Vac	90-280	90-280	90-280	90-280
Control current range		mA	4-25	4-25	4-25	4-25
Pick-up voltage		Vac	90	90	90	90
Drop-out voltage		Vac	10	10	10	10
Input resistance		K Ohms	16-25	16-25	16-25	16-25
RMS on-state current	I_T	A	10	16	25	40
Mains control Volt		Vac	24-240	24-240	24-240	24-240
Repetitive peak off state voltage	V _{drm}	V _{pk}	600	600	600	600
Zero turn-on voltage		Vac	35	35	35	35
On-state voltage drop	V _{tm}	Vac	1.6	1.6	1.8	1.8
Off-state leakage current @ rated voltage	I _{drm}	mA	5	5	5	5
Peak one cycle surge Current (Non-Rrep)	I _{TSM}	A	100	250	1000	1000
Holding current	I _H	mA	75	120	250	250
Critical rate of rise of off state Voltage	dv/dt	V/μs	200	250	500	500
Thermal resistance (junction to case)	R _{thjc}	°C/W	1.5	1.3	0.43	0.43
Frequency range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Storage temperature	T _s	°C	- 30 to + 100	- 30 to + 100	- 30 to + 100	- 30 to + 100
Operating temperature	T _o	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Turn-on time	T-on	ms	40	40	40	40
Turn-off time	T-off	ms	80	80	80	80
Fusing current	I _T ²	A ² S	72	128	3700	3700

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : DIN 30A

Input

Output


Din Ready SSR (660 VAC)
10 ~ 40 Amps

INPUT : DC Control,
OUTPUT : Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Input: DC Control (TTL or CMOS Compatible) • Output: Back-to-Back SCR (No configuration) • Opto Isolation 2500VAC (4000 V optional) • Zero voltage turn-on or Random turn-on • Built-in safety cover • Input reverse voltage protection • Built in snubber for high DV/DT • DIN mount or back plate mounting • LED indicator showing relay 'ON' status

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KD' in place of 'D'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	DIN 30D 661000	DIN 30D 661600	DIN 30D 662500	DIN 30D 664000
Control Voltage Range		Vdc	3-32	3-32	3-32	3-32
Control current range		mA	8-30	8-30	8-30	8-30
Pick-up voltage		Vdc	3.0	3.0	3.0	3.0
Drop-out voltage		Vdc	1.0	1.0	1.0	1.0
Input resistance			Current regulator	Current regulator	Current regulator	Current regulator
RMS on-state current	IT	A	10	16	25	40
Mains control volt		Vac	48-660	48-660	48-660	48-660
Repetitive peak off state voltage	Vdrn	Vpk	1200	1200	1200	1200
Zero turn-on voltage		Vac	35	35	35	35
On-state voltage drop	V _{TM}	Vac	1.6	1.6	1.8	1.8
Off state leakage current @ rated voltage	Idrm	mA	5	5	5	5
Peak one cycle surge Current (Non-Rrep)	I _{TSM}	A	100	250	1000	1000
Holding Current	I _H	mA	75	120	250	250
Critical rate of rise of off-state voltage	dv/dt	V/μs	200	200	700	700
Thermal resistance (junction to case)	R _{thjc}	°C/W	1.8	1.3	0.43	0.43
Frequency range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Storage temperature	T _s	°C	- 30 to + 100	- 30 to + 100	- 30 to + 100	- 30 to + 10
Operating temperature	T _o	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 8
Turn-on time	T-on	ms	10	10	10	10
Turn-off time	T-off	ms	10	10	10	10
Fusing current	I _T ²	A ² S	72	128	3700	5000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.


Din Ready SSR (660 VAC)
10 ~ 40 Amps

INPUT : AC Control,
OUTPUT : Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Input: AC Control • Output: Back-to-Back SCR (No configuration) • Opto Isolation 2500VAC (4000 V optional) • Zero voltage turn-on or Random turn-on • Builtin safety cover • Built in snubber for high DV/DT • DIN mount or back plate mounting • LED indicator showing relay 'ON' status

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KA' in place of 'A'.

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS			
Parameter	Symbol	Unit	DIN 30A 661028	DIN 30A 661628	DIN 30A 662528	DIN 30A 664028
Control voltage range		Vac	90 - 280	90 - 280	90 - 280	90 - 280
Control current range		mA	4 - 25	4 - 25	4 - 25	4 - 25
Pick-up voltage		Vac	90	90	90	90
Drop-out voltage		Vac	10	10	10	10
Input resistance		K Ohms	16 - 25	16 - 25	16 - 25	16 - 25
RMS on-state current	I_T	A	10	16	25	40
Mains control volt		Vac	48 - 660	48 - 660	48 - 660	48 - 660
Repetitive peak off state voltage	V _{drm}	V _{pk}	1200	1200	1200	1200
Zero turn-on voltage		Vac	35	35	35	35
On-state voltage drop	V _{tm}	Vac	1 . 6	1 . 6	1 . 8	1 . 8
Off-state leakage current @ rated voltage	I _{drm}	mA	5	5	5	5
Peak one cycle surge Current (Non-Rrep)	I _{TSM}	A	100	250	1000	1000
Holding current	I _H	mA	75	120	250	250
Critical rate of rise of off state voltage	dv/dt	V/μs	200	200	700	700
Thermal resistance (junction to case)	R _{thjc}	°C/W	1.8	1.3	0.43	0.43
Frequency range	f	Hz	47 ~ 63	47 ~ 63	47 ~ 63	47 ~ 63
Storage temperature	T _s	°C	- 30 to + 100	- 30 to + 100	- 30 to + 100	- 30 to + 100
Operating temperature	T _o	°C	- 30 to + 80	- 30 to + 80	- 30 to + 80	- 30 to + 80
Turn-on time	T-on	ms	40	40	40	40
Turn-off time	T-off	ms	80	80	80	80
Fusing current	I _T ²	A ² S	72	128	3700	5000

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : DIN 30A



Input

Output



Schematic

Mechanical Drawing



Highlights

- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package
- PCB Mountable
- Pins are polarised


Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS
Parameter	Unit	107 AI 035022
Control Voltage	Vac	180-280
Typical Input Current	mA	6.0
Must Turn On Voltage	Vac	180
Must Release Min. Voltage	Vac	160
Typical I/P impedance	Ohms	46 K
Load Voltage Range	Vdc	3-30
Rated Load Current	mA	50
Minimum load current	mA	0.1
Maximum off-state leakage current	mA	10
Typical On-state Voltage drop	Vdc	1.5
Maximum Turn-On Time	mSec	20
Maximum Turn-Off Time	mSec	25
Dielectric Strength (I/P - O/P Insulation)	Vrms	4000
Operating Temperature Range	°C	-40 to +80
Storage Temperature Range	°C	-40 to +100




Schematic

Mechanical Drawing



4 & 5 Input
1 Output(-) & 2 Output (+)
3 Logic



Highlights


- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package
- PCB Mountable
- Pins are polarised

Electrical Specification @ TA = 25°C


ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS	
Parameter	Symbol	Unit	107AI 035011 - 24	107AI 035011-24(M1S)
MUST TURN ON VOLTAGE	V _{aa} AC		85 - 120	85 - 120
TYPICAL INPUT CURRENT		mA	1.5 - 6.0	1.5 - 6.0
MUST RELEASE MIN. VOLTAGE	V _{AC}		0 - 80	0 - 80
FREQUENCY RANGE		Hz	47 - 63	47 - 63
TYPICAL I/P IMPEDANCE		OHMS	20 - 30	20 - 30
LOAD VOLTAGE RANGE	V _{dc}		30.0 - —	—
RATED LOAD CURRENT		mA	— - 50.0	50.0
MAXIMUM OFF-STATE LEAKAGE CURRENT @ 30VDC		mA	— - 100	— - 100
LOGIC SUPPLY		VDC	5 - 24	5 - 24
LOGIC CURRENT @ 5VDC		mA	— - 1.5	— - 1.5
LOGIC CURRENT @ 24VDC		mA	— - 12.0	— - 12.0
TYPICAL ON-STATE VOLTAGE DROP	V _{dc}		— - 0.3	— - 0.3
MAXIMUM TURN-ON TIME		mSec	TYP 15.0 - 20	TYP 15.0 - 20
MAXIMUM TURN-OFF TIME		mSec	TYP 15.0 - 25	TYP 15.0 - 25
DIELECTRIC STRENGTH				
(I/P - O/P INSULATION)	V _{rms}		2500	
OPERATING TEMPERATURE RANGE		°C	-40°C to 80°C	-40°C to 80°C
STORAGE TEMPERATURE RANGE		°C	-40°C to 100°C	-40°C to 100°C




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package
- PCB Mountable
- Pins are polarised


Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS
Parameter	Symbol	Unit	107AO 240300
Control Voltage		VDC	3-32
Typical Input Current		mA	25
Must Turn On Voltage		VDC	3.0
Must Release Min. Voltage		VDC	1.0
Typical I/P impedance		OHMS	Current Regulator
Reverse polarity protection			Yes
LED			Green
Load Voltage Range		VAC	24 - 240
Rated Load Current (ref derating curve)		A	3
Minimum load current		mA	100
Maximum off-state leakage current		mA	10
Typical On-state Voltage drop		V	1.6
Surge current peak (1 cycle)		A	208
Transient protection			
(static dv/dt not to exceed blocking voltage)		V/mSec	30
Maximum zero voltage offset		VAC	35
Blocking voltage (peak)		Vdrm	600
Frequency range		Hz	47 - 63
I squared t for fusing (t= 8.3ms)		I² t	259
Maximum Turn-On Time		mSec	10
Maximum Turn-Off Time		mSec	10
Thermal Resistance(Junction to case)		°C/W	2.0
Dielectric Strength (I/P - O/P Insulation)		Vrms	2500
Operating Temperature Range		°C	-40°C to +80°C
Storage Temperature Range		°C	-40 to +100


*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.



Schematic



Mechanical Drawing



Highlights


- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package
- PCB Mountable
- Pins are polarised

Electrical Specification @ TA = 25°C


ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS		
Parameter	Symbol	Unit	107DI 030348 - 24	107DI 032505-24	107DI 030300 - 24
Control Voltage		VDC	33 - 48	5-32	3 - 32
Typical Input Current		mA	8.0	6	12
Must Turn On Voltage		VDC	33.0	5.0	3.5
Must Release Min. Voltage		VDC	28.0	1.0	1.0
Max revese control voltage		VDC	-48.0		
Typical I/P impedance		OHMS	6 K	5 K ohms	3 K ohms
Load Voltage Range		Vdc	30	3-30	3 -30
Rated Load Current		mA	30	25	30
Minimum load current		mA	0.1	0.1	0.1
Maximum off-state leakage current		μA	100	10	10
Typical On-state Voltage drop		Vdc	0.4	0.4	1.5
Maximum Turn-On Time		mSec	5	5	5
Maximum Turn-Off Time		mSec	5	5	5
Logic Voltage range		VDC	5 - 24	5 - 24	5 - 24
Logic current		mA	12	12	12
Dielectric Strength (I/P - O/P Insulation)		Vrms	2500	2500	2500
Operating Temperature Range		°C	-30 to +80	-40 to +80	-40 to +80
Storage Temperature Range		°C	-30 to 100	-40 to +100	-40 to +100




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package
- PCB Mountable
- Pins are polarised


Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS
Parameter	Symbol	Unit	107DO 060300
Control Voltage		VDC	3.5 - 32
Typical Input Current		mA	25
Must Turn On Voltage		VDC	3.5
Must Release Min. Voltage		VDC	1.0
Typical I/P impedance		OHMS	1.8 K ohms
Load Voltage Range		Vdc	3-60
Rated Load Current(ref thermal derating curve)		A	3
Minimum load current		mA	50
Maximum off-state leakage current		mA	10
Typical On-state Voltage drop		V	1.6
Maximum Turn-On Time		mS	1
Maximum Turn-Off Time		mS	2
Typical power dissipation		Watt/A	1.5
Dielectric Strength (I/P - O/P Insulation)		Vrms	2500
Operating Temperature Range		°C	-40°C to +80°C
Storage Temperature Range		°C	-40 to +100




JDA241000


Schematic



Mechanical Drawing



Derating Curve



Highlights

- Compatible to TTL and CMOS logic
- LED indication
- Industrial standard package
- PCB Mountable
- Pins are polarised

Electrical Specification @ TA = 25°C

ELECTRICAL SPECIFICATIONS			PRODUCT PART NUMBERS
Parameter	Symbol	Unit	106 AO 240500
Control Voltage		VDC	3-32
Typical Input Current		mA	25
Must Turn On Voltage		VDC	3.0
Must Release Min. Voltage		VDC	1.0
Typical I/P impedance		OHMS	Current Regulator
Reverse polarity protection			Yes
LED INDICATION			Green
Load Voltage Range		VAC	24 - 240
Rated Load Current (ref derating curve)		A	5
Minimum load current		mA	75
Maximum off-state leakage current		mA	10
Typical On-state Voltage drop		V	1.6
Surge current peak (1 cycle)		A	300
Transient protection			
(static dv/dt not to exceed blocking voltage)		V/mSec	300
Maximum zero voltage offset		VAC	35
Blocking voltage (peak)		Vdrms	600
Frequency range		Hz	47 - 63
I squared t for fusing (t = 8.3ms)		I² t	510
Maximum Turn-On Time		mSec	8.3
Maximum Turn-Off Time		mSec	8.3
Typical power dissipation		W/A	1.2
Dielectric Strength (I/P - O/P Insulation)		Vrms	3750
Operating Temperature Range		°C	-40°C to +100°C
Storage Temperature Range		°C	-40°C to +125°C

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

DIN Ready SSR (240-600V)
10 Amps

NEW-No Heat Sink SSR




INPUT : DC Control,
OUTPUT : Back - to - Back SCR

ERI®


Series : DIN25D




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Input: DC/AC Control • Output: Back-to-Back SCR (NO configuration) • Opto Isolation 2500VAC (4000 V optional)
- Zero voltage Turn-on or Random Turn-on • Built-In safety cover(IP 20 Protection) • Input reverse voltage protection
- Built-In snubber for high DV/DT • DIN mount or back plate mounting • LED indicator showing relay 'ON' status

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KD' in place of 'D'.

ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS
Parameter	Unit	DIN 25D 661000
Control Voltage	VDC	3 - 32
Max Input Current	mA	35
Must Turn On Voltage	VDC	3
Must Release Min. Voltage	VDC	1
Nominal I/P impedance	OHMS	Current regulator
Reverse polarity protection		yes
Load Voltage Range	VAC	48 to 600
Rated Load Current (rms)	A	10
Minimum load current	mA	75
Maximum off-state leakage current (rms)	mA	10
Typical On-state Voltage drop (rms)	Vac	1.6
Surge current peak (1 cycle)	A	500
Transient protection		
(static dv/dt not to exceed blocking voltage) V/mSec		200
Maximum zero voltage offset	VAC	35
Blocking voltage (peak)	Vdrn	660
Maximum Turn-On Time	mSec	8.3
Maximum Turn-Off Time	mSec	8.3
Dielectric Strength (I/P - O/P Insulation)	Vrms	2500
Operating Temperature Range	°C	-30 to +80
Storage Temperature Range	°C	-40 to +100

DIN Ready SSR (240-600V)

10 Amps


NEW-No Heat Sink SSR

INPUT : AC Control,
OUTPUT : Back - to - Back SCR


ERI®




Schematic



Mechanical Drawing



Derating Curve



Highlights

- Input: DC/AC Control • Output: Back-to-Back SCR (NO configuration) • Opto Isolation 2500VAC (4000 V optional)
- Zero voltage Turn-on or Random Turn-on • Built-In safety cover(IP 20 Protection) • Input reverse voltage protection
- Built-In snubber for high DV/DT • DIN mount or back plate mounting • LED indicator showing relay 'ON' status

Electrical Specification @ TA = 25°C

Note: For Random T - On SSR, add letter 'KA' in place of 'A'.

ELECTRICAL SPECIFICATIONS		PRODUCT PART NUMBERS
Parameter	Unit	DIN 25A 661024
Control Voltage	VAC	90 to 280 (80 to 140)
Typical Input Current @120VAC	mA	10mA@120VAC 16mA@240VAC
Must Turn On Voltage	VAC	90
Must Release Min. Voltage	VAC	10
Typical I/P impedance	OHMS	20K
Load Voltage Range	VAC	48 - 600
Rated Load Current (rms)	A	10
Minimum load current	mA	75
Maximum off-state leakage current (rms)	mA	10
Typical On-state Voltage drop (rms)	Vac	1.6
Surge current peak (1 cycle)	A	500
Transient protection		
(static dv/dt not to exceed blocking voltage)	V/mSec	200
Maximum I2T fusing current	A	1250
Maximum zero voltage offset	VAC	35
Blocking voltage (peak)	Vdrms	660
Maximum Turn-On Time	mSec	8.3
Maximum Turn-Off Time	mSec	8.3
Dielectric Strength (I/P - O/P Insulation)	Vrms	2500
Operating Temperature Range	°C	-30 TO +80
Storage Temperature Range	°C	-40 to +100

*Our policy is one of continuous development and specifications are subject to change without notice. Warranty is limited to a period of one year for relay value only.

Series : DIN25A

Input

Output